

PSI PARKER SYSTEMS, INC.

THE ENVIRONMENTAL SUPPLY HOUSE...SINCE 1970.

TURBIDITY CURTAIN

TYPE II, PERVIOUS

Turbidity Curtain Type II - Should be used in areas where there may be slow to moderate running current (up to 2 knots or 3.5 feet per second) and/or wind and wave action.

Our SiltMaster Type II is specifically manufactured to meet and/or exceed US Department of Transportation (DOT) and other regulatory requirements for turbidity control in Type II fastwater (rivers, streams, lakes) conditions.

Type II curtain makes an excellent choice for silt and sediment control where moving water, winds, and waves are present.

SPECIFICATIONS

Type II Turbidity Curtain

- Beltech 200 Geotextile
- Marine Grade Expanded Polystyrene (EPS) Floatation
- Lace Connectors
- 5/16" Hot-Dipped Galvanized Proof Coil Chain
- 5/16" Galvanized Cable Coated to 3/8"
- Geotextile Skirt customized to specifications
- Choice of 50' or 100' sections standard



APPLICATIONS

- Marine Construction
- Slow to Moderate Current
- Silt and Sediment Control
- Containment & diversion of floating debris, trash and vegetation

Parker Systems, Inc.
PO Box 6380, Chesapeake VA 23323

Distributed by:
Colonial
Construction Materials
Ph. 800-436-6287

Due to the many variables to be considered at a site, we recommend that you consult with our field tested experts to obtain the best possible results.