



Technical Specifications for

Nedia KoirLog™ 12HD (High Density with Coir Netting)

Nedia KoirLog™ 12HD is a 100% natural coconut fiber log used for shoreline and stream channel applications to dissipate the impact of wave action and flowing water, protect erodible soils and encourage vegetation growth through biotechnical stabilization.

Property	Typical Value	
	English Units	Metric Units
Nominal Diameter	12 in	30 cm
Nominal Length*	10' or 20'	3.05m or 6.10m
Unit Weight	7.0 lbs/ft	10.4 kg/m
Core Density	9.0 lbs/cu.ft	145 kg/cu.m
Wave Height	12 in	30 cm
Water Velocity	8.0 ft/s	2.4 m/s
Outer Netting Material	3 ply coir with 0.40 in. Dia.	3 ply coir with 1 cm. Dia.
Outer Netting Breaking Strength	100 lbs	445 N
Outer Netting Mesh Size	2" x 2" Rhombic mesh with handknotted junctions	
Inner Core	Unsorted, double cleaned, well-graded coir fiber	

**Actual length may be 3" to 6" shorter due to natural shrinkage of coir fiber from moisture loss and other factors.*

Distributed by:



800-436-6287

www.colonial-materials.com

The above information is to the best of our knowledge accurate, but it is not intended to be considered a guarantee. Any implied warranty for a particular use or purpose is excluded. Nedia Enterprises, Inc. will not be liable for any type of damage or losses, directly or indirectly for failure of this product. All test results and properties were obtained from independent laboratory testing. If the product does not meet the above properties, and if a written notice is given to Nedia Enterprises, Inc., within seven days of delivery date, the product will be replaced or refunded.