

REINFORCING SUCCESS

WINFAB 370HP is manufactured using high tenacity polypropylene yarns that are woven to form a dimensionally stable network, which allows the yarns to maintain their relative position.

WINFAB 370HP resists ultraviolet deterioration, rotting, and biological degradation and is inert to commonly encountered soil chemicals.


PRODUCT DATA SHEET WINFAB 370HP











PROPERTY	TEST METHOD	MARV ENGLISH	MARV METRIC
Wide Width Tensile	ASTM D4595	3,600 x 3,300 lbs/ft	52.5 x 48.2 kN/m
Wide Width Tensile @ 2% Strain	ASTM D4595	540 x 540 lbs/ft	7.9 x 7.9 kN/m
Wide Width Tensile @ 5% Strain	ASTM D4595	1,500 x 1,560 lbs/ft	21.9 x 22.8 kN/m
Wide Width Tensile @ 10% Strain	ASTM D4595	2,400 x 2,400 lbs/ft	35 x 35 kN/m
UV Resistance (500 hrs)	ASTM D4355	80%	80%
Apparent Opening Size*	ASTM D4751	30 US Std. Sieve	0.60 mm
Permittivity	ASTM D4491	.52 sec ⁻¹	.52 sec ⁻¹
Permeability	ASTM D4491	0.05 cm/sec	0.05 cm/sec
Water Flow Rate	ASTM D4491	40 gpm/ft ²	1,630 lpm/m ²

*Maximum Average Roll Valve

PROPERTY		TYPICAL ENGLISH	TYPICAL METRIC
Roll Dimensions	-	15 ft x 300 ft	4.6 m x 91.5 m
Roll Area	-	500 yd²	418 m²

Disclaimer: WINFAB assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. WINFAB disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.

© 2018 WINFAB





www.colonial-materials.com P. 800-436-6287



