

# PSI PARKER SYSTEMS, INC.

THE ENVIRONMENTAL SUPPLY HOUSE...SINCE 1970.

## TURBIDITY CURTAIN

## TYPE I, IMPERVIOUS

Turbidity Curtain Type I - Should be used in protected areas where there is no current and the area is sheltered from wind and waves.

Our SiltMaster Type I is specifically manufactured to meet and/or exceed US Department of Transportation (DOT) and other regulatory requirements for turbidity control in Type I calm (lakes, ponds, canals) conditions.

## SPECIFICATIONS

### Type I Turbidity Curtain

- 22 oz. PVC-Coated Polyester
- Marine Grade Expanded Polystyrene (EPS) Floatation
- Lace Connectors
- 5/16" Hot-Dipped Galvanized Proof Coil Chain
- PVC Skirt customized to specifications
- Choice of 50' or 100' sections standard



## APPLICATIONS

- Marine Construction
- Slow to No Current
- Silt and Sediment Control
- Containment & diversion of floating debris, trash and vegetation

Parker Systems, Inc.  
PO Box 6380, Chesapeake VA 23323

Distributed by:

**Colonial**  
Construction Materials  
Ph. 800-436-6287

Due to the many variables to be considered at a site, we recommend that you consult with our field tested experts to obtain the best possible results.