

PSI PARKER SYSTEMS, INC.

THE ENVIRONMENTAL SUPPLY HOUSE...SINCE 1970.

TURBIDITY CURTAIN

TYPE I, PERVIOUS

Turbidity Curtain Type I - Should be used in protected areas where there is no current and the area is sheltered from wind and waves.

Our SiltMaster Type I is specifically manufactured to meet and/or exceed US Department of Transportation (DOT) and other regulatory requirements for turbidity control in Type I calm (lakes, ponds, canals) conditions.

SPECIFICATIONS

Type I Turbidity Curtain

- Beltech 200 Geotextile
- Marine Grade Expanded Polystyrene (EPS) Floatation
- Lace Connectors
- 5/16" Hot-Dipped Galvanized Proof Coil Chain
- Geotextile Skirt customized to specifications
- Choice of 50' or 100' sections standard



APPLICATIONS

- Marine Construction
- Slow to No Current
- Silt and Sediment Control
- Containment & diversion of floating debris, trash and vegetation

Parker Systems, Inc.
PO Box 6380, Chesapeake VA 23323

Distributed by:

Colonial
Construction Materials
Ph. 800-436-6287

Due to the many variables to be considered at a site, we recommend that you consult with our field tested experts to obtain the best possible results.