



## TURBIDITY CURTAIN

## TYPE II, IMPERVIOUS

Turbidity Curtain Type II - Should be used in areas where there may be slow to moderate running current (up to 2 knots or 3.5 feet per second) and/or wind and wave action.

Our SiltMaster Type II is specifically manufactured to meet and/or exceed US Department of Transportation (DOT) and other regulatory requirements for turbidity control in Type II fastwater (rivers, streams, lakes) conditions.

Type II curtain makes an excellent choice for silt and sediment control where moving water, winds, and waves are present.

## SPECIFICATIONS

### Type II Turbidity Curtain

- 22 oz. PVC-Coated Polyester
- Marine Grade Expanded Polystyrene (EPS) Floatation
- Lace Connectors
- 5/16" Hot-Dipped Galvanized Proof Coil Chain
- 5/16" Galvanized Cable Coated to 3/8"
- PVC Skirt customized to specifications
- Choice of 50' or 100' sections standard



## APPLICATIONS

- Marine Construction
- Slow to Moderate Current
- Silt and Sediment Control
- Containment & diversion of floating debris, trash and vegetation

Parker Systems, Inc.  
PO Box 6380, Chesapeake VA 23323

Distributed by:

**Colonial**  
Construction Materials  
Ph. 800-436-6287

Due to the many variables to be considered at a site, we recommend that you consult with our field tested experts to obtain the best possible results.