

12 Gauge Chain Link

Mesh Size	Inches mm	2 in 50.8 mm	1 3/4 in 44.5 mm	1 1/4 in 31.8 mm	1 in 25.4 mm	5/8 in 15.8 mm	1/2 in 12.7 mm	3/8 in 9.5 mm	Wire Breakload lbf	Wire Breakload N
12 gauge	0.105 in 2.67 mm	R	R	R, P	R	S, HI	S, HI	S, HI	650	2890

General Applications:

C = Commercial I = Industrial HI = Heavy Industrial
 R = Residential T = Tennis Court S = Security
 HS = High Security NM = Not Manufactured
 P = Residential Swimming Pool Fabric

Polymer coated wire gauge is designated by the steel wire core gauge not the coated finish.

Chain link fence fabric height: The standard heights produced are 3 feet up 12 feet. Some fabrics can be special ordered in heights up to 20 feet.

Chain link fabric selvage (top and bottom edge finish): Knuckled selvage refers to bending the two adjacent pairs of wire back into a tight loop. Twist selvage refers to twisting the adjacent pairs of wire into a close helix of the equivalent to three full twists. The twist selvage has two sharp points for the purpose of enhancing security, for security applications the twist selvage can be specified for the top and bottom selvage. For consumer safety consideration, chain link fabric having 2 inch mesh in heights less than 72 inches and fabric having a mesh size than 2 inches are manufactured having a knuckled finish at the top and bottom, "K&K". Chain link fabric having 2 inch mesh in heights 72 inches and greater is manufactured having a knuckle finish at one selvage and a twist selvage at the other "K&T".

Safety Alert: Specify K&K selvage for 2 inch mesh in heights 72 inches and greater for play area, parks, play fields, ball fields, pools, etc.

Made in America 

Distributed by Colonial Construction Materials Inc.

1071 Merchants Lane Oilville, VA 23129

Ph. 800-436-6287

www.colonial-materials.com