

SOILPAM™ TRACKSACK™

Wheel Track Management for Pivot and Lateral Irrigation Systems

PRODUCT DESCRIPTION

SOILPAM TRACKSACK consists of soil-stabilizing, water-soluble polymer tablets in mesh bags. The tablets contain a high quality, high purity linear anionic copolymer. When wetted, TRACKSACKS are effective in reducing the depth and severity of ruts caused by a moving irrigation system. Use of this product also reduces pivot maintenance costs while increasing water infiltration in and around the wheel tracks in the soil.

APPLICATION

Water from the irrigation spray heads slowly dissolves the tablets within the mesh bag. Polymer-laden water drips from the bottom of the bag into the wheel tracks as the system moves, thus stabilizing the soil in and around the track, while protecting against deep ruts, clumps, and ponding.

TRACKSACKS are packaged 8 bags, with various number of tablets, per delivered box. For maximum efficiency, each SOILPAM TRACKSACK should be hung in good water flow directly over the wheel tracks, with the smallest bag hung on the inside tower ,graduating to the largest bag on the outside tower.

SEE REVERSE FOR APPLICATION RATES

TYPICAL PROPERTIES

Appearance of Tablets	Disk-Shaped, White Solid
Approx. Weight of 1 Tablet	1 oz.
Approx. Diameter of 1 Tablet	1.5 in.
pH (0.5% Solution)	5 - 9
Storage Temperature	30 °F - 90 °F
Shelf Life**	12 months

**When stored inside between 30 °F - 90 °F.

HANDLING AND STORAGE

Avoid contact with skin and eyes. Wash hands and face before breaks and immediately after handling the product. Keep containers tightly closed. Keep in a dry, cool, and well-ventilated place.

PACKAGING

- 35 lb. plastic lined, sealed box

HEALTH AND SAFETY

SOILPAM TRACKSACK is non-hazardous, however, precautions should be taken to avoid inhalation, ingestion, or contact with skin or eyes.

SPILLS: Dry tablet spills should be left dry, swept up, and discarded.

Caution: Polymer spills are extremely slippery when wet. If the tablets become wet when spilled, an absorbent material should be applied to the spill, then swept up, and discarded.

Both wet and dry spills should be discarded according to local, state, or federal regulations.



SOILPAM™ TRACKSACK™

TYPICAL APPLICATION RATE*

Per 57 ft. of wheel track length	1 Tablet (1 oz.)
Per 1,006 ft. of wheel track length	16 Tablets (1 lb.)

*These are only provided as starting points. Rates will vary according to soil type, amount of water flow, ground slope, soil conditions, etc.

SAMPLE APPLICATION RATES

Example 1: 8-Tower System with 156' (47.5m) Spans

Approx. Number of Applications	1	2	3	4	5	6	7	8
Lb. (kg) per bag	1.2 (0.5)	1.8 (0.8)	2.9 (1.3)	3.9 (1.8)	4.9 (2.2)	5.9 (2.7)	6.9 (3.1)	7.9 (3.6)
Tablets	13	31	47	63	78	94	110	125

Example 2: 7-Tower System with 179' (54.5m) Spans

Approx. Number of Applications	1	2	3	4	5	6	7	
Lb. (kg) per bag	1.2 (0.5)	2.5 (1.1)	3.7 (1.7)	5.0 (2.3)	6.3 (2.9)	7.5 (3.4)	8.8 (4.0)	
Tablets	20	40	60	80	100	120	140	

For additional information, please refer to the Safety Data Sheet (SDS)

All statements, information and data given herein are believed to be accurate, but are presented without warranty expressed or implied. Statements concerning possible use are made without representation or warranty that any such use is free of patent infringement, and is not a recommendation to infringe on any patent. The user should not assume that all safety measures are indicated or that other measures may not be required. Any determination of the suitability of a particular product for any use contemplated by the user is the sole responsibility of the user.