



STRIPE SOLVENT-BASE MARKING PAINT

A fast drying marking paint designed to be sprayed in an inverted position. Produces vivid marks, does not clog, and is safe for grass. The solvent based formulation works well in low temperatures. Meets APWA color standards and is VOC compliant. May be sprayed by hand or with the Z-605 marking gun or Z-606 marking wand.

Suggested Uses:

Utility marking;
Golf courses
Landscaping
Construction sites
Surveying
Mining

Packaging:

Cans per case	12
Shipping weight per case	20 lbs.
Container	20 fluid ounce can
Label weight	17 ounces (482 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 500 linear feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	36%
MIR value	0.82, cannot exceed 0.85
HAPs content	0
Storage Temperature	40-90F
Application Temperature	50-100F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes @ 72F
	15 minutes@ 35F

****Curing/Recoat time is extended with multiple coats and excessively thick coats****

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
20-631	Clear Line Saver	043281001816
20-651	Aluminum	043281001403
20-952	White	043281002066
20-953	Precaution Blue	043281002103
20-954	Fluorescent Red	043281006651
20-955	Safety Green	043281002073
20-957	Fluorescent Orange	043281006668
20-958	Fluorescent Red/Orange	043281006675

Available Colors:

Part #	Description	UPC Code
20-968	Fluorescent Green	043281001397
20-969	Fluorescent Blue	043281001380
20-970	Alert Orange	04328100
20-971	Safety Red	043281002097
20-976	Hi Visibility Yellow	04328100
20-978	Utility Yellow	043281006682
20-979	Hot Pink Fluorescent	043281006699